

# PRODUCT INFORMATION

## COMPOSITION FLOOR RESTORER Penetrating Vinyl / Acrylate Seal

---

**DESCRIPTION** **Composition Floor Restorer** is a thermo-plastic acrylic emulsion seal for composition and linoleum floors. It is easier to use than solvent systems and meets health, safety, and environmental standards better than a solvent-borne system. Composition Floor Restorer is superior in chemical and detergent resistance.

**USE** Use **Composition Floor Restorer** to seal and restore old asphalt tile, vinyl asbestos, vinyl rubber, cork and linoleum. It is an easy to use, aqueous system, that will not attack the tile floor like a solvent system.

**DIRECTIONS** **Preparation:** Remove all old floor wax and finish using a wax stripper (**Top Gun**). Be sure all finish is removed. Rinse floor thoroughly and allow to dry.

**Application:** For best results, apply seal liberally to a clean, dry floor with a chenille applicator from a wax pan. Smooth over surface with long, even strokes. Avoid puddles, but keep applicator well saturated. Clean applicator immediately, using T.Q. Finish & Wax Remover solution. Note: on very porous floors, a second coat may be required.

**Drying:** Under normal conditions, seal dries in one hour. Allow to dry thoroughly before applying any floor finishes.

**Finishing:** Apply one or two coats of floor finish as directed after seal has dried completely. To maintain floor, damp mop and/or spray buff.

**WARNING** Avoid contact with eyes. Always read label before using product. KEEP OUT OF THE REACH OF CHILDREN.

*Note: See Material Safety Data Sheet for Additional Specifications and First Aid Information.*

1050 Revised 121410